



## Technical Data // FRSL1.5-DR

Push-In Type | Protective Conductor Clamp

3 Connections



### Wire Sizes

Solid min	0.2 mm <sup>2</sup>
Solid max	1.5 mm <sup>2</sup>
Stranded (flexible) min	0.2mm <sup>2</sup>
Stranded (flexible) max	1.5 mm <sup>2</sup>
Stranded with ferrule min	0.2 mm <sup>2</sup>
Stranded with ferrule max	1.5 mm <sup>2</sup>
Clamping range min	0.2mm <sup>2</sup>
Clamping range max	1.5 mm <sup>2</sup>

### Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

### Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

### Dimensions


Stripped length	12.0 mm
Width	4.1 mm
Length	59.5 mm
Height TS35 x 7.5	43.0 mm

### ELECTRICAL DATA

#### General

Cross connection channels	2
---------------------------	---

### COLOURS



GREEN/YELLOW



## Technical Data // FRSL1.5-DR

Push-In Type | Protective Conductor Clamp

3 Connections

### CONNECTION DIAGRAM



### ORDER DATA

Article Designation	Article Number	PU
FRSL1.5-DR-GREEN/YELLOW	43204.2	100

### ACCESSOIRES

Article Designation	Article Number	PU
End Plate FAP1.5/3A	493401.2	20
Four-Way Covers FAD1.5/4/B	493425.8	20
End Stopn ZES35/2	493811.2	50
Quick Labelling PSB4/50	494820.7	500

### RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage			
Rated current			
Rated wire size	AWG 24-16	AWG 24-16	1.5 mm <sup>2</sup>
Rated impulse voltage			8 kV
Pollution degree			3