



Technical Data // FTR2.5-DR-ST

Push-In Type | Disconnect Terminal Block
3 Connections



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions



Stripped length	10.0 mm
Width	5.1 mm
Length	82.0 mm
Height TS35 x 7.5	59.5 mm

ELECTRICAL DATA

General

Cross connection channels	1
---------------------------	---

COLOURS

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015

**Technical Data // FTR2.5-DR-ST**

Push-In Type | Disconnect Terminal Block

3 Connections

CONNECTION DIAGRAM**ORDER DATA**

Article Designation	Article Number	PU
FTR2.5-DR-ST-BEIGE	43262.2	100
FTR2.5-DR-ST-BLUE	43262.5	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate FAPT2.5/3A	493482.2	50
Cross-Connection insulated FQI2.5/2	493462.8	50
Cross-Connection insulated FQI2.5/3	493463.8	50
Cross-Connection insulated FQI2.5/4	493464.8	20
Cross-Connection insulated FQI2.5/5	493465.8	20
Cross-Connection insulated FQI2.5/6	493466.8	20
Cross-Connection insulated FQI2.5/7	493467.8	20
Cross-Connection insulated FQI2.5/8	493468.8	10
Cross-Connection insulated FQI2.5/9	493469.8	10
Cross-Connection insulated FQI2.5/10	493460.8	10
Four-Way Covers FAD2.5/4/B	493426.8	20
Disconnect Plug ZDS1/ZTR	493612.2	20
Disconnect Plug ZDS2/ZTR	493613.2	20
Disconnect Plug ZDS3/ZTR	493614.2	20
Disconnect Plug ZDS4/ZTR	493615.2	20
End Stopn ZES35/2	493811.2	50
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage	300 V	300 V	400 V
Rated current	15 A	15 A	18 A
Rated wire size	AWG 20-12	AWG 20-12	2.5 mm ²
Rated impulse voltage			6 kV
Pollution degree			3