

Technical Data // SRMB4/2-FW1-2B

Screw Type | Through Terminal Block

4 Connections Direct mounting With labelling on both sides



Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	4.0 mm ²
Clamping range min	0.2mm ²
Clamping range max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-2

Temperatures

Working temperature	-40 - 105 °C
---------------------	--------------

Dimensions

Stripped length	9.0 mm
Width	6.0 mm
Height	23.0 mm
Length	26.5 mm
Length hole direct mounting	19.4 mm

**PTR HARTMANN**

A Phoenix Mecano Company

Technical Data // SRMB4/2-FW1-2B

Screw Type | Through Terminal Block

4 Connections Direct mounting With labelling on both sides

COLOURS

 BEIGE, similar RAL 1019 BLUE, similar RAL 5015

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
SRMB4/2-FW1-2B-BEIGE	42343.2	50
SRMB4/2-FW1-2B-BLUE	42343.5	50

ACCESSOIRES

Article Designation	Article Number	PU
External Cross-Connector insulated AQ12/6/11	492125.0	50
External Cross-Connector insulated AQ13/6/11	492126.0	50
External Cross-Connector insulated AQ14/6/11	492140.0	10
External Cross-Connector insulated AQ110/6/11	492141.0	10

RATINGS

Ratings	UR	CSA	IEC
Rated voltage	300 V	300 V	400 V
Rated current	30 A	25 A	32 A
Rated wire size	AWG 22-12	AWG 22-12	4.0 mm ²
Rated impulse voltage			6 kV
Pollution degree			3