

Technical Data // ZR2.5-DRL-T

Tension Spring Type | Through Terminal Block

2x2 Connections



Wire Sizes

Solid min	0.5 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.5mm ²
Stranded (flexible) max	4.0 mm ²
Stranded with ferrule min	0.5 mm ²
Stranded with ferrule max	2.5 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions

Width	5.1 mm
Length	83.6 mm
Height TS35 x 7.5	39.0 mm

ELECTRICAL DATA

General

Test pick off	2
---------------	---

COLOURS

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015
	ORANGE, similar RAL 2003



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZR2.5-DRL-T

Tension Spring Type | Through Terminal Block

2x2 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZR2.5-DRL-T-BEIGE	43503.2	100
ZR2.5-DRL-T-BLUE	43503.5	100
ZR2.5-DRL-T-ORANGE	43503.3	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAP2.5/4A	493702.2	50
Four-Way Covers ZAD2.5/4/B	493706.0	20
End Stopn ZES35	493748.2	50
Test Adapter ZTA2.5	493740.2	10
Quick Labelling PSB5/50	494600.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage	600 V	600 V	800 V
Rated current	27 A	27 A	24 A
Rated wire size	AWG 20-12	AWG 20-12	2.5 mm ²
Rated impulse voltage			8 kV
Pollution degree			3