



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // ZR4-DRL

Tension Spring Type | Through Terminal Block
4 Connections



Wire Sizes

Solid min	0.5 mm ²
Solid max	6.0 mm ²
Stranded (flexible) min	0.6mm ²
Stranded (flexible) max	6.0 mm ²
Stranded with ferrule min	0.5 mm ²
Stranded with ferrule max	4.0 mm ²

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Working temperature	-40 - 120 °C
---------------------	--------------

Dimensions

Width	6.1 mm
Length	93.0 mm
Height TS35 x 7.5	42.0 mm

ELECTRICAL DATA

General

Cross connection channels	2
Test pick off	2

COLOURS

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015
	ORANGE, similar RAL 2003
	GREEN, similar RAL 6018
	RED, similar RAL 3001

**PTR HARTMANN**


A Phoenix Mecano Company

Technical Data // ZR4-DRL

Tension Spring Type | Through Terminal Block

4 Connections

CONNECTION DIAGRAM



ORDER DATA

Article Designation	Article Number	PU
ZR4-DRL-BEIGE	43517.2	100
ZR4-DRL-BLUE	43517.5	100
ZR4-DRL-ORANGE	43517.3	100

ACCESSOIRES

Article Designation	Article Number	PU
End Plate ZAP4/4A	493705.2	50
Cross-Connection insulated ZQI4/2	493720.8	50
Cross-Connection insulated ZQI4/3	493721.8	50
Cross-Connection insulated ZQI4/4	493722.8	20
Cross-Connection insulated ZQI4/5	493723.8	20
Cross-Connection insulated ZQI4/6	493724.8	20
Cross-Connection insulated ZQI4/7	493725.8	20
Cross-Connection insulated ZQI4/8	493726.8	10
Cross-Connection insulated ZQI4/9	493727.8	10
Cross-Connection insulated ZQI2.5/9	493717.8	10
Four-Way Covers ZAD4/4/B	493707.0	20
End Stopn ZES35	493748.2	50
Test Adapter ZTA4	493741.2	10
Quick Labelling PSB6/50	494702.7	500

RATINGS

Ratings	CSA	CSAus	IEC
Rated voltage	600 V	600 V	800 V
Rated current	35 A	35 A	32 A
Rated wire size	AWG 20-10	AWG 20-10	4.0 mm ²
Rated impulse voltage			8 kV
Pollution degree			3